

# CONTROLLERS & SPECIAL VALVES

## GEM-FLOW™ | G75-C

Irrigation Controller | 1, 2 & 4 Valves



### Technical Data

Operating temperature	-10° to 60°C
Mounting	<p>Various mounting options:</p> <ul style="list-style-type: none"> <li>• Directly on a 28mm diameter solenoid in horizontal or vertical position with adaptor</li> <li>• Wall mounting with four screws</li> <li>• Accessories provided</li> </ul>
Electrical	<p>Powered by single 9V alkaline battery; use best quality to ensure at least one year's autonomous operation.</p> <ul style="list-style-type: none"> <li>• Back-up memory</li> <li>• Low battery warning</li> <li>• Power saving LCD</li> <li>• Battery included</li> </ul>
Solenoid	Compatible with G75 4Ω latch operator
Valve	Can operate any valve equipped with 3/4" UNEF solenoid cavity (Richdel® type)
Software	<ul style="list-style-type: none"> <li>• 24 hours real time clock</li> <li>• See 'Programming key features' table</li> </ul>
Options	<ul style="list-style-type: none"> <li>• Solar panel</li> <li>• Charger</li> <li>• Accurate clock (low time drift)</li> </ul>
Standard / Certification	CE
Standard protection class	<ul style="list-style-type: none"> <li>• Dust and watertight</li> <li>• IP67 and NEMA 4X</li> </ul>



G75 One Valve

G75 Two Valves

G75 Four Valves



Size	A	B	C
3/4"	145	110	81
1"	153	110	81
1-1/2"	166	160	127
2"	166	170	127

### Mounting Options

Wall mounting



Horizontal mounting



# GEM-FLOW™ | G75-C | Irrigation Controller | 1, 2 & 4 Valves

## Programming Key Features

One Valve	Two Valves	Four Valves
Once daily, at the same time	Up to three starts per day	Up to three starts per day
Once daily on selected days	Starts select	Starts select
Three starts per day	Day select	Day select
OFF	Season adjustment 10% - 200%	Season adjustment 10% - 200%
	OFF	OFF
		Master valve will be opened for each command

## How to Order

G75-C	-	TYPE OF CONTROLLER <sup>(1)</sup>	-	VALVE 1 <sup>(1)</sup>
		One valve	1	No valve
		Two valves	2	00
		Four valves	4	40
				1/2" BSP
				1/2" NPT
				3/4" BSP
				3/4" NPT
				1" BSP
				1" NPT
				1-1/2" BSP
				1-1/2" NPT
				2" BSP
				2" NPT
				<b>G75-A *</b>

### \* G75-A

TYPE	PORT	FUNCTION	MANUAL OVERRIDE	ORIFICE
with flange	1/8" BSP	2W NC	None	1.0 <sup>(2)</sup>
Brass	1/8" NPT	3W NC		1.2
	1/4" BSP <sup>(2)</sup>	3W NO		1.6
	1/4" NPT <sup>(2)</sup>			3

### 1) Example: G75-C-160

GEM-FLOW™ G75 One Valve controller, 1" BSP

(1) Only for One valve controller type. Choose "00" for Two and Four valve controller types

(2) Brass only

\* To order controllers manufactured according to your specific requirements, please contact our technical sales department