CONTROLLERS & SPECIAL VALVES

OCTOPUS[™]


Filter Backwash Controller


- Filtration backwash controller 1+3 or 1+10 stations
- Mobile app in various languages •
- Wireless operated by smartphone .
- · Main valve output is included
- Backwash by DP, Time interval or Manual
- Upstream & Downstream pressure sensors


Technical Data

Communication protocol	Wireless BLE
App Downloading	Google play
Mechanical	 Operating temperature: -10°C to 60°C Outdoor UV protection "H" proof pressure: 10 bar (145 PSI) "H" pressure must be ≥ "L" pressure
Electrical	 DC units are powered by 8 x C type alkaline batteries or 12V DC
Mounting	 Pressure ports 8mm High pressure port is marked by the letter "H" on the housing Wall mounting with four ø3.5 plastic-screws or the two M5 (low profile) self-tapping screws
Features	 Differential pressure up to 10 bars Time interval Manual operation Alarm and backwash output for communication with irrigation controller Data logger
Options	 Mounting bracket measurements upon request
Standard protection class	 IP65 Dust and watertight
Solenoid	G75-A 12 OHM, G75-A3P-4 OHM, G75-P-12 OHM, GEM-A3P-IL 2 wires only










How to Order

G75-Octopus

TYPE	
1+3 stations	03
1+10 stations	10

Example: G75-Octopus-10

Octopus™, 10 stations + 1 Main valve





* To order controllers manufactured according to your specific requirements, please contact our technical sales department





OCTOPUS[™] | Filter Backwash Controller

The App

Available in 9 languages: English | Arabic | French | German | Hebrew | Portuguese | Spanish | Turkish | Italian

